



D1260 Series LCD Keypads



- ▶ Integrated user Help windows to simplify operation
- ▶ Illuminated four-line display

Each D1260 Series Keypad model is an SDI bus compatible device that works with G Series Control Panels. Each keypad model has an illuminated keypad, a bright four-line by 20-character English language liquid crystal display (LCD), and a sounder that emits eight warning tones.

Note The D1260 Series Keypads are available exclusively to Bosch Certified Security Dealers (BCSD).

Functions

LCD Display

Every D1260 Series Keypad model uses words, numbers, and symbols to show the status of the security system. When several events occur, each model shows each event in order of priority.

Keys

Each D1260 Series Keypad model has 10 numeric keys, two function keys, and eight soft keys. Use the [COMMAND] key in combination with numeric keys to perform a function. Use the [ENTER] key to enter your passcode. Use the eight soft keys to select a menu and associated functions.

Audible Tones

The sounder emits eight distinct warning tones. You can adjust the volume. You can also use a passcode to silence the tone.

The tones include:

- Burglary Signal: Steady high-pitched bell tone during alarm.
- Fire Signal: Pulsed high-pitched bell tone during fire alarm.
- Entrance Warning: Intermittent beep tones during entry delay periods.
- Exit Warning: Intermittent beep tones during exit delay periods.
- Invalid Key Buzz: Buzz tone when an invalid key is pressed.
- Keypad Encoding Tone: Muted beep tone as each key is pressed.
- Trouble Buzzer: Two-tone warble during a trouble event.
- Watch Tone: Intermittent beep tone when a watch point is faulted.

National Security Systems Inc (800)457-1999

Certifications and Approvals

Keypad Model	Certifications and Approvals
D1260, D1260B, D1260BLK, D1260R, and D1260W	UL1076 Proprietary Alarm Units UL864 Control Unit Accessories, System UL1610, UL1635 Central Station Alarm Units UL985 Control Units and Accessories-Household System Type UL1023 Household Burglar Alarm System Units UL609, Local Alarm Units UL365, Police Station Alarm Units
D1260 Only	CSFM

Installation/Configuration Notes

Compatibility Information

Control Panels	D9412G, D7412G, D7212G, D9412, D7412, D7212, and D9112 with firmware versions 6.40 or higher.
----------------	---

Mounting Considerations

- Do not mount any of the D1260 Series Keypad models in a location exposed to direct sunlight. Direct sunlight can interfere with screen visibility and damage internal components.
- Do not mount any of the D1260 Series Keypad models in damp locations.

Power Supplies

A compatible control panel supplies the power and data requirements to a D1260 Series Keypad model through a simple four-wire connection. To determine if an additional power supply is needed, use the operation and installation manual for the specific control panel and refer to the current rating chart for standby battery calculations.

Wiring Considerations

Use 1.2 mm (18 AWG) or 0.8 mm (22 AWG) wire. Resistance cannot exceed 14 Ω . Each D1260 Series Keypad model includes a wiring assembly of four color-coded flying leads and one female four-pin connector.

Technical Specifications

Power Requirements

Voltage:	Nominal 12 VDC
Standby Current:	Idle 200 mA Maximum 250 mA, with the sounder and display backlight at maximum

Keypad

Dimensions for D1260, D1260W, D1260R, and D1260BLK:	10.9 cm x 20 cm x 2.6 cm (4.3 in. x 7.9 in. x 1 in.)
Dimensions for D1260B:	12.6 cm x 20.9 cm x 3.2 cm (5 in. x 8.2 in. x 1.3 in.)

Weight for All Models:	439 g (15.5 oz)
------------------------	-----------------

Indicators:	Illuminated keys Warning and indicating tones
-------------	--

Material

D1260, D1260W, D1260R, and D1260BLK:	GE CYCOLOY® C1110. UL94-HB Fire Rated
D1260B:	CHI MEI POLYLAC® PA-757 with UV Stabilizer. UL94-HB Fire Rated

Connections

Connections:	4-wire flying lead for data and power
Resistance:	14 Ω maximum

Display Screen

Type:	Backlit LCD
Size:	8.6 cm x 3.6 cm (3.4 in. x 1.4 in.) 4 lines x 20 characters

Environmental Considerations

Humidity:	95% \pm 2% at 49°C (120°F)
Operating Temperature:	0°C to +49°C (+32°F to +120°F)
Use:	Intended for indoor use

Number of...

D1260 Series Keypad Models per Control Panel:	8 supervised 32 unsupervised
---	---------------------------------

Trademarks

CYCOLOY® is a registered trademark of General Electric Company.
POLYLAC® is a registered trademark of CHI MEI Industrial Corporation, LTD.
Plexiglas® is a registered trademark of Arkema.

Note The D1260 Series Keypads are available exclusively to Bosch Certified Security Dealers (BCSD).

Ordering Information

D1260 LCD Keypad Off-white classic case.	D1260
---	-------

National Security Systems Inc (800)457-1999

Ordering Information

D1260W LCD Keypad White classic case.	D1260W
D1260R LCD Keypad Red classic case.	D1260R
D1260BLK LCD Keypad Black classic case.	D1260BLK
D1260B LCD Keypad White and gray modern case.	D1260B
Hardware Accessories	
D54B-1260 Brass Flush Mount Kit Back box and polished brass faceplate used with D1260 Series Keypad models.	D54B-1260
D54C-1260 Stainless Steel Flush Mount Kit Back box and stainless steel faceplate used with D1260 Series Keypad models.	D54C-1260
D55 Keypad Desk Stand Portable desk stand in smoke colored Plexiglas®.	D55
D56 Surface Mount Conduit Box White surface mount box.	D56
D56R Red Surface Mount Conduit Box Red surface mount box.	D56R

Americas:

Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 27 83955
Fax: +31 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by